


[THE NEXT]

COB Shop Lighter Series

Technical Operation Data

• POWER:60W



	LW-SLW60-AN0W	LM-SLD60-AN0W
LUMINOUS FLUX	5300lm	5500lm
COLOR	Warm White	DAY White
CCT	3000K	4000K
CRI	>83	>83
REFLECTOR	Mirror	Mirror
RADIANCE ANGLE	100° (X)x 60° (Y)	100° (X)x 60° (Y)
VOLTAGE(AC)	220-240V 50/60Hz	220-240V 50/60Hz

	LM-SLN60-AN0W
LUMINOUS FLUX	5500lm
COLOR	Neutral white
CCT	5000K
CRI	>83
REFLECTOR	Mirror
RADIANCE ANGLE	100° (X)x 60° (Y)
VOLTAGE(AC)	220-240V 50/60Hz

	LM-SLW60-BN0W	LM-SLD60-BN0W
LUMINOUS FLUX	5200lm	5400lm
COLOR	Warm white	Day white
CCT	3000K	4000K
CRI	>93	>93
REFLECTOR	Nano-Coating	Nano-Coating
RADIANCE ANGLE	100° (X)x 60° (Y)	100° (X)x 60° (Y)
VOLTAGE(AC)	220-240V 50/60Hz	220-240V 50/60Hz

	LM-SLN60-BN0W
LUMINOUS FLUX	5400lm
COLOR	Neutral white
CCT	5000K
CRI	>93
REFLECTOR	Nano-Coating
RADIANCE ANGLE	100° (X)x 60° (Y)
VOLTAGE(AC)	220-240V 50/60Hz

Remark:

A: Mirror reflector

B: Nano-coating reflector

Please contact us for other specification information.

[APPOLLO]

COB Shop Lighter Series

[Appollo]


The most powerful downlight in the market, up to 60w, equipped with special aluminum fin to ensure perfect heat dissipation. LEDs lumen decays less than 5% after 5 years!



Dimensional Drawing

Dia.	260
H	160
C	Ø220

*Unit = mm
*Cut Hole size can be +/- 5mm




Diameter (Dia.)

Environmental Properties

Operating Temperature	-10°C ~ +40°C
Storage Temperature	-40°C ~ +60°C
Life time	50,000 hours

Mechanical Properties

Body	Aluminum
Base	External Driver
Weight	1.2kg




Cut Hole (C)

[APPOLLO]

COB Shop Lighter Series

Technical Operation Data

• POWER:45W, 4000K




	LM-SLW45-DN0W6	LM-SLD45-DN0W6
LUMINOUS FLUX	3800lm	4000lm
COLOR	Warm White	DAY White
CCT	3000K	4000K
CRI	>83	>83
REFLECTOR	Nano-coating	Nano-coating
RADIANCE ANGLE	60°	60°
VOLTAGE(AC)	220-240V 50/60Hz	220-240V 50/60Hz

LM-SLN45-DN0W6

LUMINOUS FLUX	4000lm
COLOR	Neutral white
CCT	5000K
CRI	>83
REFLECTOR	Nano-coating
RADIANCE ANGLE	60°
VOLTAGE(AC)	220-240V 50/60Hz

• POWER:60W, 4000K



	LM-SLW60-DN0W6	LM-SLD60-DN0W6
LUMINOUS FLUX	5400lm	5500lm
COLOR	Warm White	DAY White
CCT	3000K	4000K
CRI	>83	>83
REFLECTOR	Nano-Coating	Nano-Coating
RADIANCE ANGLE	60°	60°
VOLTAGE(AC)	220-240V 50/60Hz	220-240V 50/60Hz

LM-SLN60-DN0W6

LUMINOUS FLUX	5500lm
COLOR	Neutral white
CCT	5000K
CRI	>83
REFLECTOR	Nano-Coating
RADIANCE ANGLE	60°
VOLTAGE(AC)	220-240V 50/60Hz

Remark:

A: Mirror reflector

B: Nano-coating reflector

Please contact us for other specification information.



Edeka Supermarket, Germany