



Cafe in Makati, Manila Philippines

[LOOPSX] NARROW ANGLE GU10 SPOT LIGHT

[LOOPSX] is an ideal replacement of 30W - 50W halogen spot lamps, with trendy appearance and concrete structure, suitable for most indoor applications.


- ◆ Power up to 6W, with 480lm brightness
- ◆ With 3 different beam angles including extremely narrow option: 10° / 25° / 36°
- ◆ GU10 powered by **LUMAN**
- ◆ Quality materials providing 35,000 hours lifetime (L70), 3 year warranty



3 YEARS IP40 RGB INDOOR

Smaller , but Bigger


High contrast in lighting effect



[LOOPSX]

NARROW ANGLE GU10 SPOT LIGHT

Dimensional Drawing



Version	GU10
Dia.	Ø50
TH	56
H	51

*Unit = mm



Environmental Properties

Operating Temperature	-10°C ~ +40°C
Storage Temperature	-40°C ~ +60°C
Life time	35,000 hours

Mechanical Properties

Body	Aluminum
Base	GU10
Weight	67g

[LOOPSX]

NARROW ANGLE GU10 SPOT LIGHT

Technical Operation Data

	LM-GU10-6W-827-xD	LM-GU10-6W-830-xD
LUMINOUS FLUX	450lm	480lm
COLOR	Super Warm	Warm White
CCT	2700K	3000K
CRI	>80	>80
DIMMING FUNCTION	Non-Dim	Non-Dim
RADIANCE ANGLE	10°/25°/ 36°	10°/25°/ 36°
VOLTAGE(AC)	85-240V 50/60Hz	85-240V 50/60Hz

	LM-GU10-6W-840-xD	LM-GU10-6W-860-xD
LUMINOUS FLUX	540lm	540lm
COLOR	Day White	Cool White
CCT	4000K	6000K
CRI	>80	>80
DIMMING FUNCTION	Non-Dim	Non-Dim
RADIANCE ANGLE	10°/25°/ 36°	10°/25°/ 36°
VOLTAGE(AC)	85-240V 50/60Hz	85-240V 50/60Hz

	LM-GU10-6W-827-xDIM	LM-GU10-6W-830-xDIM
LUMINOUS FLUX	450lm	480lm
COLOR	Super Warm	Warm White
CCT	2700K	3000K
CRI	>80	>80
DIMMING FUNCTION	Dimmable	Dimmable
RADIANCE ANGLE	10°/25°/ 36°	10°/25°/ 36°
VOLTAGE(AC)	85-240V 50/60Hz	85-240V 50/60Hz

	LM-GU10-6W-840-xDIM	LM-GU10-6W-860-xDIM
LUMINOUS FLUX	540lm	540lm
COLOR	Day White	Cool White
CCT	4000K	6000K
CRI	>80	>80
DIMMING FUNCTION	Dimmable	Dimmable
RADIANCE ANGLE	10°/25°/ 36°	10°/25°/ 36°
VOLTAGE(AC)	85-240V 50/60Hz	85-240V 50/60Hz

Remark:

'x' (Beam angle) =10°/ 25° / 36°

Please contact us for more specification information.

[LOOPSX]

NARROW ANGLE GU10 SPOT LIGHT

Technical Operation Data

	LM-GU10-6W-927-xD	LM-GU10-6W-930-xD
LUMINOUS FLUX	420lm	450lm
COLOR	Super Warm	Warm White
CCT	2700K	3000K
CRI	>90	>90
DIMMING FUNCTION	Non-Dim	Non-Dim
RADIANCE ANGLE	10°/25°/ 36°	10°/25°/ 36°
VOLTAGE(AC)	85-240V 50/60Hz	85-240V 50/60Hz

	LM-GU10-6W-940-xD	LM-GU10-6W-960-xD
LUMINOUS FLUX	480lm	480lm
COLOR	Day White	Cool White
CCT	4000K	6000K
CRI	>90	>90
DIMMING FUNCTION	Non-Dim	Non-Dim
RADIANCE ANGLE	10°/25°/ 36°	10°/25°/ 36°
VOLTAGE(AC)	85-240V 50/60Hz	85-240V 50/60Hz

	LM-GU10-6W-927-xDIM	LM-GU10-6W-930-xDIM
LUMINOUS FLUX	420lm	450lm
COLOR	Super Warm	Warm White
CCT	2700K	3000K
CRI	>90	>90
DIMMING FUNCTION	Dimmable	Dimmable
RADIANCE ANGLE	10°/25°/ 36°	10°/25°/ 36°
VOLTAGE(AC)	85-240V 50/60Hz	85-240V 50/60Hz

	LM-GU10-6W-940-xDIM	LM-GU10-6W-960-xDIM
LUMINOUS FLUX	480lm	480lm
COLOR	Day White	Cool White
CCT	4000K	6000K
CRI	>90	>90
DIMMING FUNCTION	Dimmable	Dimmable
RADIANCE ANGLE	10°/25°/ 36°	10°/25°/ 36°
VOLTAGE(AC)	85-240V 50/60Hz	85-240V 50/60Hz

Remark:

'x' (Beam angle) =10° / 25° / 36°

Please contact us for more specification information.

